



Floor Decal Installation & Maintenance



- FOR BEST ADHESION, CLEAN AND PREP SURFACE THOROUGHLY PRIOR TO APPLICATION
- FLOOR DECALS SHOULD BE APPLIED AT TEMPERATURES BETWEEN 40°F - 90°F (4.44°C – 32.22°C)
- DO NOT SCRUB, WAX, OR POLISH GRAPHIC FOR 24 HOURS AFTER APPLICATION

Suitable Floor Types


Avery floor decals are designed to be applied to smooth indoor surfaces. This system was developed for commercial tile floors but may be used on sealed concrete, sealed wood, and certain ceramic tile.

Avoiding Tripping Hazards


For best results, the decal should be applied to floors in good condition. To minimize potential tripping hazards, follow the tips below:



Do not apply to rough, uneven surfaces or broken tiles.




Do not apply over wide gaps between tiles.



Keep edges out of gaps between tiles.



Reapply or replace decals that bubble or pucker.



Replace decals that have lifted edges or excessive wear.



PREPARATION


Floor surface must be clean and adequately dry prior to application of decal. Your flooring must be firmly attached to the subfloor. Before applying this product, we recommend you first test this product in an “inconspicuous area” to assure suitability of the decal for your specific flooring.



APPLICATION


Once your floor is adequately prepped, follow these steps to ensure best results:

Step 1. Peel



Peel the backing paper (release liner) 1” from the top of the sheet and crease to expose a thin strip of adhesive.

Step 2. Apply



Carefully position the decal. Adhere the exposed edge to the floor. Pull the liner away, applying the decal as you go.

Step 3. Squeegee



Using a squeegee, start at the middle of the decal and work out toward the edges with firm pressure to remove trapped air.

⚠ Do not clean, scrub, wax or polish for at least 24 hours.



MAINTENANCE

- When selecting a floor wax, ensure it meets or exceeds ASTM D 2047 standards for appropriate static coefficient of friction (.5 min). This ensures proper slip resistance.
- Prevent damage to decals by avoiding heavy-equipment traffic (i.e. fork lifts, pallets).

⚠ Avoid risk of injury by immediately removing a decal with a lifted edge!



REMOVAL

- To remove decal start at one edge and pull at an angle less than 45 degrees, using short quick strokes. If wax is accumulated around the edge, a putty knife may be required to lift the decal's edge.
- To remove in smaller sections, use a knife to slit the edge and remove each section separately.
- Decal removal may pull up some of the wax on tile floors. Clean and re-wax that area to create a level surface.

NOTE: For easier removal, apply light heat to one edge of the decal as you pull up.



AVERY® WARRANTY AND LIMITED REMEDY FOR AVERY FLOOR DECALS

Avery Products Corporation (“Avery”) makes the following warranty and limited remedy in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose:

Avery® warrants that the Avery Floor Decals, when constructed, installed, maintained, and removed in accordance with Avery’s written instructions, will for a period up to 180 days after installation (i) be suitable and safe for its intended use as a medium for floor advertising, as determined by industry-recognized standards for slip resistance; (ii) excepting normal and expected wear, maintain its original brightness, color, and image quality; and (iii) will adhere to Avery’s recommended floor surfaces and be removable without damage to such surfaces.

As a sole and exclusive remedy, Avery will replace or refund the price of any AVERY® Floor Decals that does not conform to this warranty.

EXCEPT FOR THE EXPRESS WARRANTIES SET FORTH HEREIN, AVERY DOES NOT MAKE ANY REPRESENTATIONS OR GRANT ANY WARRANTIES, EXPRESS OR IMPLIED, EITHER IN FACT OR BY OPERATION OF LAW, BY STATUTE OR OTHERWISE, AND SPECIFICALLY DISCLAIMS ANY OTHER WARRANTIES, WHETHER WRITTEN OR ORAL, OR EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF QUALITY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR USE OR PURPOSE.

AVERY SHALL NOT BE LIABLE HEREUNDER UNDER ANY CONTRACT, NEGLIGENCE, STRICT LIABILITY OR OTHER LEGAL OR EQUITABLE THEORY FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES INCLUDING, LOSS OF BUSINESS, PROFITS OR GOODWILL ARISING OUT OF THE USE OR INABILITY TO USE THIS PRODUCT. This warranty and limited remedy does not limit or exclude any claims for personal injury allegedly caused by Avery.

Avery Customer Service: (800) 942-8379